

REVISIONS TO THE 2009-2011 RULE BOOK, SPECIFICATIONS FOR NASCAR LATE MODEL

The following is a list of changes or revisions made after the release Official 2009-2011 Rule Book:

Changes indicated as follows:

Date / Division / Rule Section / ~~Deleted Rule~~ / **New Revision**

January 1, 2010.

LATE MODELS

12. SUSPENSION, (k) Tread Width Requirements: **(1) Front and rear tread width shall not exceed a maximum of 75" measured from the outside of rim at bead of tire to outside of rim at bead of tire at spindle height. The tread width will be determined by measuring from the left rear outside wheel bead surface to the right rear outside wheel bead surface at spindle height.** ~~Front and rear tire width shall not exceed a maximum of 75" measured from outside of rim at bead of tire to outside of rim at bead of tire at spindle height.~~

January 1, 2010.

LATE MODELS

5. DETAILED ENGINE REQUIREMENTS, Air Intake: (air filter):

(10) Shields or deflectors of any type near the air cleaner not permitted, **except, it is permissible to attach a shield to the front area of the cleaner housing up to a maximum of half the air cleaner circumference; the shield must not be higher than the height of the air cleaner filter.**

(11) Tubes, funnels, or any device that may control the flow of air will not be permitted inside of the filter or between the air filter housing and the carburetor.